

You print. We plant.

TASKalfa Pro 15000c & TASKalfa Pro 15000c/B

Rethink your workflows with our superfast eco inkjet production printers.





Welcome to Kyocera!

Kyocera Group is a global company continually creating new value at the cutting edge of technology. It is active in multiple business segments including Industrial & Automotive components, Semiconductor components, Electronic Devices, Communications, R&D and more.

Kyocera Document Solutions has been supporting businesses for more than 60 years with innovative and sustainable printers, multifunctional products and solutions that help them to put knowledge to work.

We are specialists in advanced cloud, ICT and managed document solutions. Our founder's pioneering philosophy guides how we work and shapes our vision for the future of the smarter workplace and for the protection of our precious planet.

Our past secures your future

For more information, visit www.kyoceradocumentsolutions.co.uk

A revolution in high-speed printing:

Our TASKalfa Pro 15000c colour inkjet and TASKalfa Pro 15000c/B mono inkjet production printers bring together more than 60 years of digital expertise and experience to meet your high-volume printing needs. These superfast inkjet production printer offers you a cost-efficient alternative to conventional printing in transactional, trans-promotional and direct mail applications. Built for speed and reliability, they feature unique print head and ink technologies developed by Kyocera. They are designed to secure the future of your business by enhancing your reputation and providing fast, sustained return on your investment.





TASKalfa Pro 15000c & TASKalfa Pro 15000c/B

Fast, high-quality output to enhance your image

The TASKalfa Pro print and copy outputs are among the fastest in the market (150 ppm for A4), with no speed reduction on heavy media stock. With additional high capacity stackers and vacuum paper feeders, paper output can reach 14,310 sheets. A print resolution of 600 x 600 dpi ensures stable image quality, while accurate front to back registration delivers consistent image positioning on every page.

- Large-capacity vacuum feed trays enable reliable transport of your media.
- The robust, durable design ensures reliable performance in demanding environments.
- High-quality components include Kyocera's own time-proven inkjet head.

Reliable throughput with lower costs

From healthcare and education to finance, marketing, postal services and government departments, the TASKalfa Pro expertly handles high volumes and critical processes. It enables secure, predictable workflows in a wide range of environments. Quick, reliable performance is combined with sector-leading energy efficiency to keep your costs down while reducing the carbon footprint of your business.

- The TASKalfa Pro holds numerous international energy certifications.
- Remote servicing and preventive maintenance optimise uptime.



Efficient input for new heights in productivity

The TASKalfa Pro was developed for high-volume printing with exceptional turnaround time. The Fiery controller manages the print queue efficiently and Managed Enterprise Output (MEO) software takes care of more complex workflows.

- Operation is simple with an intuitive touch-panel interface.
- Most maintenance and fine adjustment can be done by the user.



Advantages



1. High Productivity

The TASKalfa Pro's non-stop production system enables continuous 150 ppm printing. Similar to plain paper, 360g/m² of thick paper can be printed non-stop for 9,000 pages.



2. Superb Print Quality

The TASKalfa Pro's inks and ink discharge technology ensure color consistency and high print quality to meet the demands of production print industry.



3. Wide Media Handling

The TASKalfa Pro productively prints on a wide variety of media sizes, weights, and types, expanding the range of profitable printing applications.



4. Optimized In-Line Option

Optimum versatility with feeding, stacking and finishing options let you customize the system that is right for your business.



5. Selectable Controllers and Applications

Enables efficient production and superior quality with the TASKalfa Pro's controller or with the optional Fiery Print Server.



6. Exceptionally Easy to Use

Maximizes productivity by letting you replace key components and consumables in moments. The integrated touch panel provides an unified and easy to use interface.



7. Eco-friendly Advantages

Inkjet printing which does not require heat to fuse toner reduces power consumption significantly. The TASKalfa Pro reflects our decades-long commitment to sustainable products and manufacturing.



8. Enhanced Security

The TASKalfa Pro is equipped with the latest security features such as user authentication, HDD data overwrite and encryption capabilities.

Reduce. Reforest. Rethink.



Find out more

- + **Reduce** your energy consumption with a device that draws just 3.5kW/hr
- + **Reforest** native woodland in the UK as you print, with PrintReleaf
- + **Rethink** what your organisation can achieve with superfast, versatile, low cost printing and ultra-efficient workflows



In partnership with

printreleaf™



BASIC SPECIFICATIONS

Engine speed (Pages per minute):

TASKalfa Pro 15000c Colour/Black – A4: 150ppm, Letter: 146 ppm, Legal/B4: 98 ppm, A3: 88ppm, Ledger: 86 ppm, SRA3: 75ppm (print only), 12" x 18": 74 ppm (print only)

TASKalfa Pro 15000c/B Black – A4: 150ppm, Letter: 146 ppm, Legal/B4: 98 ppm, A3: 88ppm, Ledger: 86 ppm, SRA3: 75ppm (print only), 12" x 18": 74 ppm (print only)

Warm-up time: 120 seconds or less (Power On), [W/DE-9100: 15 minutes or less]

First Page Out: Copy: 5.0 seconds or less Print: 5.5 seconds or less

Resolution: 600 x 600 dpi; 600 x 1200 dpi

Memory / Hard Disk Drive: 4.5 GB RAM/ 32 GB SSD / 1 TB HDD Standard

Duplex: Standard Stackless Duplex Supports A5/ Statement to SRA3/12" x 18", 60 – 300gsm

Standard Output Tray: A5R/Statement – 13" x 19.2"/ 500 Sheets, (A6R : Right output tray)

Typical Electricity Consumption (TEC):

7.5 kWh/week [120W/220V]

Integrated accounting:

Dimensions (W x D x H): 965 mm x 740 mm x 1220 mm.

Weight: 308 kg or less.

Maximum Monthly Duty Cycle:

1,000,000 Pages per Month

PAPER SUPPLY

Standard Paper Source: Dual 500 Sheet Trays, Dual 1,500 Sheet Trays, 150 Sheet MPT, Auto Selection / Switching

Optional Paper Sources: Dual

2,440 Sheet (PF-9100)

Max 2 units 550 Sheet Multi-Media

Paper Feeder (PF-9110)

Paper Capacity: Standard: 4,150

Sheets; Maximum: 14,310 Sheets

Paper Size: Tray: A5/5.5" x 8.5" – 12" x

18"; MPT: A6/5.5" x 8.5" – 13" x 19.2"

Paper Weight: Trays / (MPT) : Max

360gsm / (Max 300gsm)

Input Materials: Plain paper / II plain paper /

II matte paper / Thick paper / Postcard / Tab

paper / Envelope / Banner paper / II media

COPY FUNCTIONS

Max. original size: A3/Ledger

Continuous copying: 1–9,999

Zoom range: 25–400 % in 1% steps

Preset magnification ratios: 5 Reductions/5

Enlargements

Exposure mode: Auto, manual: 16 steps

Image adjustments: Text + Photo, Photo, Text,

Map, Printed document

Features: Scan-once-copy-many, electronic sort,

2in1, 4in1, image repeat, page numbering, cover

mode. booklet copy, interrupt copy, form overlay,

margin shift, auto cassette change, Skip blank page,

ID card copy

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0,

Scan-to-USB Host, Scan-to-box, Network TWAIN,

WSD scan

(WIA Driver Network)

Scan speed: (A4, 300 dpi, Dual Scan) 220 images

per minute;

(A4, 300 dpi, Simplex Scan) 120 images per minute

Scan resolution: 600 x 600 dpi, 400 x 400 dpi,

300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x

100 dpi; 256 greyscales per colour

Max. scan size: A3, Ledger, Banner up to 2,200 mm

Original recognition: Text, photo, text + photo,

light text/

fine line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS,

Encrypted PDF, High compression PDF, PDF/A-1a/b,

PDF/A-2a/b/u,

Features: Colour scan, Auto Colour Select,

integrated address book, Active Directory

support, encrypted data transfer, multi send

(e-mail, fax, SMB/FTP folder, print) at once,

Blank page skip, Specified colour removal

PRINT SPECIFICATIONS

Standard Controller: QorIQ T1042

(Quad Core) / 1.2GHz

PDLs / Emulations: PCL6 (PCL-XL / PCL5c),

KPDL3 (PS3), PDF, OpenXPS, XPS, PPML

Print Resolution: Up to 600 x 1200 dpi

Fonts: 136 KPDL3, 93 PCL6, 8

Windows Vista, 1 Bitmap.

OS Compatibility: Windows: XP/Vista/7/8/8.1/10/

Server 2003/Server 2008/Server 2008 R2/

Server 2012/Server 2012 R2; Novell NetWare

3.x/4.x/5.x/6.x; Mac Sun OS 4.1.x; Solaris 2.x;

AIX; HP-UX; (LPR)OS 10.x; AirPrint Enabled.

Interfaces: Standard: 10/100/1000BaseTX,

Hi-Speed USB 2.0, 4 USB Host Interfaces

Network Print and Supported Protocols: TCP/

IP, FTP, LPR, NetBEUI, IPv4, IPv6, IPsec, SSL,

HTTP, LPD, IPP, RawPort, LLLD, SNTP, DHCP,

SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print

Drivers: KX Driver

OPTIONAL FIERY CONTROLLER

PRINTING SYSTEM 50

Fiery System Version: Fiery FS300 Pro

Configuration: External

Memory: 16GB (8GB x 2)

CPU: Intel Xeon E5-2637 (3.5 GHz

up to 3.7 GHz with turbo)

HDD: 500 GB + 2 x 2 TB SATA

CONSUMABLES

Average continuous Ink yield in accordance with

5% coverage A4.

IK-7115K, IK-7115C, IK-7115M, IK-7115Y

Staples: SH-10 for BF-9110, SH-14 for DF-7130

ENHANCEMENTS

PF-9100: Vacuum Feed Paper Feeder

PF-9110: Multi Bypass Tray

DE-9100: Drying & Decurl Unit

ST-9100: High Capacity Stacker

DF-9100: Document Finisher

BF-9110: Booklet Finisher

SL-9100: Status Indicator Light

PH-7C: Hole Punch

AK-9110: Relay Unit between Paper Feeder and

Printer

AK-9120: Relay Unit between Stacker and Finisher

AK-9130: Relay unit between PF-9100 & 2nd PF-

9100

AK-9140: Relay kit for PF-9110

KYOCERA Document Solutions (U.K.) Limited

Eldon Court
75-77 London Road
Reading
Berkshire RG1 5BS

Tel: 03330 151855
Email: info@duk.kyocera.com

kyoceradocumentsolutions.co.uk



Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.